

DECLARATION OF PERFORMANCE

Nº 007KKE2017

GRES ARAGON

1. Unique identification code of the product type

Type, batch or serial Lumber or any other element allowing identification of the product

Extruded ceramic tiles, with water absorption 3%<E_b≤6% type 7*

2. Intended use(s)

For internal and external walls and floorings

3. Name or registered trade mark, and contact address of the manufacturer

Gres de Aragón, S.A.

Carretera Escatrón Km.9 44600 ALCAÑIZ (TERUEL) ESPAÑA

4. System(s) of assessment and verification of constancy of performance (AVCP)

System 4

- 5. Name and identification number of notified laboratory, if relevant
- 6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	A1 > 950 N 35 <rd≤ 2="" 45="" class="" npd="">1 N/mm² Pass EN 14411:2016</rd≤>
Breaking strength	> 950 N	
Slipperiness, as:	35 <rd< 45<="" td=""></rd<>	
Pendulum UNE:ENV:12633:2003 Anexx A	00 110	
Tactility	NPD	
Bond strength/adhesion, for:	>1 N/mm²	
Cementitious adhesive, type C2	>1 N/IIIII	
Thermal shock resistance	Pass	
Durability for::		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufactured identified in point 3.

Signed for and on behalf of the manufacturer by:

José Ramón Hernando Encuentra Gres de Aragón S.A. Representative

Jamon /ernander

GRES ARAGÓN, s. A.
CIF: A-50000843
Ctra. Escatrón, 9
44600 ALCAÑIZ (Teruell)
Tel. +34 978 83 05 11

Alcañiz, 6th February 2017

(*)Type 7 corresponds to Esmaltado Classic (Teka, Pisa and Parma), Vulcano, Stone and Columbia series